



La tubería SADMx HI-TEC<sub>MR</sub> está disponible en longitudes de 6.10 (20´) y 7.63 (25´) pies.

<b>DIÁMETRO NOMINAL pulg.</b>	<b>DIÁMETRO INTERIOR mm</b>	<b>DIÁMETRO EXTERIOR mm</b>	<b>PESO MÁXIMO EN KILOS</b>	<b>LONGITUD DE TRAMOS</b>
<b>30"</b>	<b>766 mm</b>	<b>872 mm</b>	<b>42.84 Kg/ ml</b>	<b>6.10 MTS (20´)</b>
<b>36"</b>	<b>920 mm</b>	<b>1070 mm</b>	<b>66.04 Kg/ ml</b>	<b>6.10 MTS (20´)</b>
<b>42"</b>	<b>1073 mm</b>	<b>1235 mm</b>	<b>84.95 Kg/ ml</b>	<b>6.10 MTS (20´)</b>
<b>48"</b>	<b>1227 mm</b>	<b>1385 mm</b>	<b>119.70 Kg/ ml</b>	<b>6.10 MTS (20´)</b>
<b>54"</b>	<b>1379 mm</b>	<b>1583 mm</b>	<b>130.41 Kg/ ml</b>	<b>6.10 MTS (20´)</b>
<b>60"</b>	<b>1532 mm</b>	<b>1732 mm</b>	<b>176.50 Kg/ ml</b>	<b>6.10 MTS (20´)</b>